

Varun Singh Bundela, Arun Patel



Abstract: While most of the focus in waste management in on municipal solid waste management, it is important to note that MSW is but a small fraction of the total amount of waste generated in the India. The municipal Solid Waste Management Rules 2016 which is the major rules that governs Solid Waste Management in India. In out Country we generated some 1,00,000 MT tons of Municipal solid waste generated daily in my country. Even through MSW in dwarfed in size (and environmental impact) by other sectors, it should be that industrial waste is created in the process of providing us with the materials things that ultimately end up in our trash. Consuming less therefore saves not only the waste that would have ended up in the municipal waste stream but it also reduces the energy, materials and waste associated with providing those items that we may be able to live without cleanly, attention needs to be directed not just at the management of consumer waste but at the completed set of processes that result in the products our society seems to demand.

Keyword: Plasma Gasification, Waste to Energy Plant, Reuse, Recycle, Effective Waste Management

I. INTRODUCTION

A. Objective of Solid Waste Management

The objective of solid waste management is to reduce the quantity of solid waste by disposed off on land by recovery of materials and converts into energy from solid waste [1-10].

B. Problems in developing countries like India: -

The waste characteristics is developing countries are known to differ considerably from that in developed countries due to different food habits, culture, traditions and socioeconomic aspects. The organic matter is found to be higher due to the use of fresh and unprocessed vegetables and has a high moisture content unpaved roads and seasonal variation in climatic conditions tend to increase the ash and soil content increasing the density of the waste. Correspondingly lower calorific value has been observed. Urban centers are mostly modern out growths of the cities with narrow winding streets requiring small slow moving vehicles for collection and transport.

Manuscript received on 24 June 2022 | Revised Manuscript received on 29 June 2022 | Manuscript Accepted on 15 July 2022 | Manuscript published on 30 July 2022.

* Correspondence Author

Varun Singh Bundela*, PhD Research Scholar, RKDF University, Bhopal (Madhya Pradesh) India. E-mail: <u>psbundela@hotmail.com</u>

Dr. Arun Patel, Professor, Department of Civil Engineering, RKDF University, Bhopal (Madhya Pradesh), India.

© The Authors. Published by Blue Eyes Intelligence Engineering and Sciences Publication (BEIESP). This is an <u>open access</u> article under the CC-BY-NC-ND license <u>http://creativecommons.org/licenses/by-nc-nd/4.0/</u>

C. Problems Being faced by urban local bodies:-

Over the years, there has been a continuous migration of people from rural and semi-urban areas to towns and cities. The proportion of population residing in urban areas has increased from 10.84% in 1901 to 25.70% in 1991. Now it is just double of the percentage. The number of class I cities has increased from 212 to 300 during 1981 to 1991, while class cites II Cities have increased from 270 to 345 during the same period. Now in the 2020 figure almost double. The increase in the population in class I cities is very high as compared to that in class II cities. The uncontrolled growth in urban areas has left many Indian cities deficient infrastructural services such as water supply, sewerage and municipal solid waste management. Barring a few progressive municipal corporation in the Country all other local bodies suffer due to non-availability of adequate expertise and experience, there by the solid waste is not properly handled resulting into creation of environmental pollution and health hazards.

II. SOLID WASTE MANAGEMENT

It involves management of activities associated with generation, storage, collection, transfer and transport processing and disposal of solid waste which is environmentally compatible adopting principles of economy, aesthetic energy and conversation. It encompasses planning, urbanization, administration, financial, legal and engineering aspect.

A. Functional Elements of MSW Management

- A. *Generation* Waste differ in the rate of generation, quantity and quality depending upon the area of generation. The quantity and quality from residential areas may not vary appreciable. On the other hand, waste from commercial and industrial area may very in quality and quantity at different times of the year. This will have a marked effect on the selection of method for its collection, processing and disposal.
- B. *Storage* The generated waste is stored within the premises in commercial and industrial areas, where as in residential areas occupants take it out and transfer to community storage basis.
- C. *Collection* Citizens deposit the wastes by the road side from where the conservancy staff transfer it to the community bins using wheelbarrow on other equipment such primary collection is common in India and other developing countries which need a large number of workers and small number of equipments [11-25].



- D. *Transportation* The material collected in community dustbins is transferred to transport vehicles for transport to processing on disposed site.
- E. The fleet transport vehicles should have sufficient capacity for average and peak loads and should be utilized at optimum levels. In big cities the material in conveyed to a transfer station from where another set of vehicles transport in furthers.
- F. *Processing and Recovery* A large quantity of waste has to be processed before suitable disposal to reduce its potential nuisance value, occasionally recovery of useful constituents is also carried out as an independent process.
- G. *Disposal* The waste may come for disposal either directly after its transportation or effect processing, Disposal could be on land or water logged area for reclamation. The different function are inter depended and interrelated which could be better managed by a system approach. Disposal method costing less may not always be the best, which may be effected by higher transport on processing cost.

B. The Case Studies of Different SWM Facility in M.P.

Integrated Solid Waste Management Facility- Vill. Pahadiya, Distt. Rewa

Location: Village Pahadiya Khasra no. 290, 292, 294,

Village Sagra, Khasra no. 2201, 2202; total area 18.35 hect. , Tehsil- Raipur Karchuliyan, District- Rewa (MP).

Google map of the project site: The project site is located in Pahadiya village on a village road which is connected to National highway NH 7 approximately 05 Kms distant passing through Raipur karchuliyan. Google map of the project site is shown below.

Latitude and longitude

24.595854 N, 81.386736 E

Site layout Site layout plan of ISWM project Villag - Pahadiya,distt. Rewa is given below.



Fig. 1 Site layout of ISWM Project Pahadiya, Rewa

C. Feasibility of the project (why this technology is adopted):

The project aims to treat/handle the municipal solid waste of 28 ULBs of Rewa, Satna and Sidhi districts in an integrated manner and cluster based approach. In this manner the cost of establishing plants at different location will be minimized and waste will be handled at single location in an integrated manner. The project proposes Waste to energy plant of 2X6 MW capacity to generate electricity from RDF produced out of solid waste thereby utilizing the waste as a resource and

minimizing the waste ultimately going to landfill. Apart from that the facility is also handling animal carcasses so as to manage the carcasses in environment friendly manner without causing public nuisance. The compost is to be made from organic fraction of solid waste which will be reused for horticulture/agriculture purposes. Thus such an integrated facility is more useful for handling large amount of solid waste in economical and environment friendly manner efficiently.

D. Area covered by ISWM facility

Municipal solid waste of 28 ULBs of Rewa, satna and Sidhi Districts is to be handled by this ISWM facility. Names of those ULBs are given below:

Table	1
I ame	
I UDIC	

		Tuble I	
Sr No.	Rewa District	Satna District	Sidhi distrcit
1	Rewa Nagar Nigam	Satna Nagar Nigam	Sidhi Municipality
2	Municipal Council, Baikunthpur, Distt. Rewa	Maihar Municipality Distt. Satna	Municipal Council Rampur Naikin, Distt. Sidhi
3	Municipal Council, Chakghat, Distt. Rewa	Municipal Council, Amarpatan, Distt. Satna	Municipal Council Churhat, Distt. Sidhi
4	Municipal Council, Teonthar, Distt. Rewa	Municipal Council, Birsinghpur, Distt. Satna	Municipal Council Majhouli, Distt. Sidhi
5	Municipal Council, Mangawan, Distt. Rewa	Municipal Council, Chitrakoot, Distt. Satna	
6	Municipal Council, Sirmour, Distt. Rewa	Municipal Council, Jaitwara, Distt. Satna	
7	Municipal Council, Semariya, Distt. Rewa	Municipal Council, Kotar, Distt. Satna	
8	Municipal Council, Hanumana, Distt. Rewa	Municipal Council, Kothi, Distt. Satna	
9	Municipal Council, Gurh, Distt. Rewa	Municipal Council, Nagod, Distt. Satna	
10	Municipal Council, Govindgarh, Distt. Rewa	Municipal Council, Ramnagar, Distt. Satna	
11	Municipal Council, Naigarhi, Distt. Rewa	Municipal Council, Rampur Baghelan, Distt. Satna	
12	Municipal Council, Mauganj, Distt. Rewa	Municipal Council Uchehra, Distt. Satna	





A map showing location/distribution of ULBs with respect to Project site is shown as follows.



Fig.2 Map showing ULBs of Rewa, Satna and Sidhi District with distances from Rewa

E. Quantity of solid waste

The total capacity of plant to handle municipal solid waste is 700 TPD. However at present approximately 150 TPD MSW is being handled at the facility. The current estimated

solid waste generation is 340 TPD in the region. Apart from MSW, the facility is also handling animal carcasses in 6-8 nos. per day from nearby localities which are incinerated in controlled conditions of operation at animal carcass plant [26-43].

III. CHARACTERISTICS OF SOLID WASTE

Mixed type of solid waste is being sent to the facility from different ULBs. It is containing food waste, vegetables, fruit peels, as organic content whereas plastic waste, tyres, inert waste, metals etc. are found as inorganic content in the waste. RDF is being prepared from combustible fraction of solid waste reaching in the facility which is further transported to cement industries for co-incineration in cement kiln. The approximation estimation of characteristics/ composition of solid waste is given below:

Table 2 Composting of MSW Of Rewa

Waste Component	% share
Food, vegetable& other organic	56.6 %
waste	
Textile	4.5
Paper, cardboard	6.6
Plastic and Polythene	18.7
Glass & Ceramic	2.9
Rubber & Leather	1.5
Wood	1.5
Stones & Bricks	7.5
Metal	0.3
Total	100%

Sr. no.	Name of unit	Capacity	Purpose	Water pollution control arrangement	Air pollution control arrangement
1	Compost plant	300 TPD	To produce compost of good quality from organic fraction of municipal solid waste	The processing of waste is done under shade and leachate collection system is provided.	The processing of waste is being done under covered shade and to mitigate the odour problem Ecosorb chemical is sprayed over the waste daily.
2	Animal carcass incinerator	200 kg/hr	To handle the dead bodies of animals without causing public nuisance.	No water pollution is there from this unit as WW generation is nil.	Three stage filters are installed to curb the chances of air pollution and adequate stack ht of 30 m is provided.
3	RDF Processing unit	500 TPD	To produce RDF which may be utilized further for energy recovery	Leachate collection system is provided.	The processing /sorting is done under covered shade.
4	Recyclables	14 TPD (5110 per year)	To recycle the metal, wood, glass and other recyclable fraction of the waste.	Recyclable fraction will be given to recyclers for processing.	Recyclable fraction will be given to recyclers for processing.
5	Waste to energy Plant	2X6 MW	To generate electricity from RDF	To be installed as WTE Plant is under construction	To be installed as WTE plant is under construction
6	Sanitary landfill	175 TPD	To dispose off leftover waste in secured manner, which cannot be reused or further processed.	HDPE liners are provided on the base and daily cover is applied in secured manner. Leachate collection system is also there.	Daily cover is applied.
7	Construction and demolition waste management facility	100 TPD	To handle C&D waste being generated from ULBs in an eco friendly manner and reuse it in new projects.	Unit is Under construction.	Unit is under construction.

Photographs of above units are given below:

(a) Compost plant:

Retrieval Number: 100.1/ijmh.K15010781122 DOI: <u>10.35940/ijmh.K1501.0781122</u> Journal Website: <u>www.ijmh.org</u>







Windrows Storage & Processing under Shade





Aerobic Compost Sorting Section Finished Compost (b) RDF Processing Unit:





RDF Processing Unit Refuse Derived fuel (RDF) content (Animal Carcass Incinerator:





Published By: Blue Eyes Intelligence Engineering & Sciences Publication (BEIESP) © Copyright: All rights reserved.







Animal Carcass Plant (200 Kg/hr Capacity) Recyclables/MRF centre:



Material Recovery facility Waste to Energy Plant: the unit is under construction.





Sanitary Landfill Leachate collection pond

A. Integrated solid waste management project Katni

Name of Project: Development of an Integrated MSW Processing and Disposal Facility at Katni by Katni MSW Management Private Limited.

Location of Project: Padarwara, Katni, Madhya Pradesh. Latitude and Longitude: (23°46'50.18" N, 80°23'20.95" E) or (23.780606° N, 80.389153° E)

Site Layout:



Fig.3 Site map showing location of Project site in India

B. Feasibility of Project (why this technology is adopted)

Safe disposal of municipal solid waste being generated in the ULBs is necessary as per SWM rules 2016. The project aims to manage the solid waste of 5 ULBs in integrated manner so as to minimize the likely environmental impact and efficiently utilize the waste as a resource wherever it may be possible. The project helps in generating RDF (Refuse Derived Fuel) which is to be used for energy recovery and organic fraction is being converted into compost by windrow composting which is further utilized /sold to farmers for horticulture / agriculture purposes. Apart from it the facility is having animal carcass incinerator plant to handle the dead bodies of animals in an environment friendly and safe manner. Thus such a facility is beneficial for handling MSW and carcasses in efficient manner and solving the need of establishing separate plant in each ULB and hence it is cost effective/economical as well.



Retrieval Number: 100.1/ijmh.K15010781122 DOI: <u>10.35940/ijmh.K1501.0781122</u> Journal Website: <u>www.ijmh.org</u>

C. Area Covered By Iswm Facility

The ISWM facility Katni is covering 5 ULBs of Katni and Jabalpur districts namely Katni Nagar nigam, Kaymore Nagar Parishad, Vijayragavgarh Nagar Parishad, Sehora Nagar Parishad (Distt Jabalpur) and Barhi nagar Parishad. A map showing relative distances of participating ULBs from Katni is given below:



Fig. 4 Relative locations of 5 ULBs with respect to Katni

IV. QUANTITY OF SOLID WASTE

At present the daily amount of MSW being collected is approximately 100 TPD however the plant capacity for projected population is about 150 TPD. Out of this collected MSW from 5 ULBs the daily amount of RDF being generated is about 50 TPD and finished compost of good/desirable quality is about 10 TPD. ULBs with approximate generation of MSW is given in following table:

	Table 4							
	Katni l	District	Jabalp	ur District				
Sr no.	Name of ULB	Approximat e quantity of MSW	Name of ULB	Approxima te quantity of MSW				
1	Katni Nagar Nigam	65 TPD	Sehora Municip ality	13.4 TPD				
2	Kymore Municipality	5.43 TPD						
3	Barhi Municipality	4.05 TPD						
4	Vijayragavga rh Municipality	2.75 PD						

.....

A. Characteristics of solid waste

Mixed type of waste is being sent to the facility which contains food waste, vegetable waste, fruit peels, plastic waste, metals and inert waste etc. Approximate physical composition of waste is given below:

		-	-	-
1	'ค	h		-
	а	IJ	IC.	-

Tuble 0	
Waste Component	% share
Food, vegetable& other organic	60.0
waste	
RDF	12.1
Textile	0.3
Paper, cardboard	0.5
Plastic and Polythene (recyclable)	0.3
Glass & Ceramic	0.1
Rubber & Leather	0.3
Stones & Bricks	0.4
Metal	0.3
Inert and non recyclables	10.6
Moisture reduction and others	15.1
Total	100%

Details of installed units with photos: The details of units is as follows- Table 6

Sr. no.	Name of unit	Capacity	Purpose	Water pollution control arrangement	Air pollution control arrangement
1	Compost plant (windrow composting)	35 TPD	To produce compost of good quality from organic fraction of municipal solid waste	The processing of waste is done under shade and leachate collection system is provided. However no leachate is observed from waste.	The processing of waste is being done under covered shade and to mitigate the odour problem organic chemicals are sprayed over the waste daily.
2	Animal carcass incinerator	350 kg/hr (dual chamber)	To handle the dead bodies of animals without causing public nuisance.	No water pollution is there from this unit as WW generation is nil.	Three stage filters are installed to curb the chances of air pollution.
3	RDF Processing unit	70 TPD	To produce RDF which may utilized further for energy recovery	Leachate collection system is provided. However no leachate is observed from waste.	The processing /sorting is done under covered shade.
4	Recyclables	15 TPD	To recycle the metal, wood , glass and other recyclable fraction of the waste.	Recyclable fraction will be given to recyclers for processing.	Recyclable fraction will be given /sold to recyclers for processing and reuse.
5	Sanitary landfill	30 TPD	To dispose off leftover waste in secured manner, which cannot be reused or further processed.	HDPE liners are provided on the base and daily cover is applied in secured manner. Leachate collection system is also there.	Daily cover is applied.

Photographs of installed units below:

(a) Compost Plant:













(b) Animal Carcass Incinerator:









Published By: Blue Eyes Intelligence Engineering & Sciences Publication (BEIESP) © Copyright: All rights reserved.



(c) *RDF Processing unit:*









(d) Recyclables/ Material Recovery Facility: Sanitary Landfill:



B. Waste To Energy Plant Jabalpur (MP)

Name of Project: Development of Waste to Energy Plant (11.5 MW) at Kathonda site, Jabalpur by M/s. Essel Infra Projects Pvt. Ltd.

Location of Project: Kathonda village, Jabalpur (M.P.) **Latitude and Longitude:** (23°12'50.3"N 79°55'03.8"E) or (23.213971N, 79.917721E)



Fig. 5 Site layout plan of Kathonda site, JabalpurSite map

C. Feasibility of Project (why this technology is adopted)

Safe disposal of municipal solid waste being generated in the ULBs is necessary as per SWM rules 2016. The project aims to manage the solid waste of Jabalpur Municipal Corporation in sustainable manner so as to minimize the likely environmental impact reducing the waste ultimately going to landfill and efficiently utilize the waste as a resource for energy recovery. At the same time the technology/process meets the regulatory requirements as per SWM rules 2016. The project helps in generating electrical energy from MSW by employing incineration process (mass burning technology) in controlled/scientific manner. In this process segregation of waste is not necessary hence reduces the operational cost and saves space where land is costly.

> Published By: Blue Eyes Intelligence Engineering & Sciences Publication (BEIESP) © Copyright: All rights reserved.





Thus such a facility is beneficial for handling huge quantity of MSW of city like Jabalpur in efficient manner following 4R principal (Reduce, Reuse, Recycle & Recover) and hence it is cost effective/economical as well. Moreover it is helpful in creating an ecosystem of circular economy which on the other hand proving it to be one of the ambitious and innovative smart cities in the country.

D. Area covered by ISWM Facility

The WTE facility is handling MSW of Jabalpur Municipal Corporation only. An indicative Google map of Jabalpur city is given below:



Fig. 7 Indicative Google map of Jabalpur City of Madhya Pradesh

Quantity of solid waste: At present the daily amount of MSW being collected and processed is approximately 600 TPD. The un-segregated MSW is processed at the facility. **Characteristics of solid waste:** Mixed type of waste is being sent to the facility which contains food waste, vegetable

waste, plastic waste, textile, metals and inert waste etc. Approximate physical composition of waste of Jabalpur city is given below:

Waste Component	% share
Food, vegetable& other biodegradable organic waste	64.3
Textile	6.3
Paper, cardboard	8.8
Plastic and Polythene	8.3
Thermacol	1.4
Glass & Ceramic	3.7
Rubber & Leather	0.3
Wood	1.6
Stones & Bricks	1.5
Metal	0.2
Inerts	3.6
Total	100%

Waste characterization in terms of calorific value from different areas of Jabalpur

Table 8

Areas	Calorific value (kcal/kg)
Commercial	2357.5
Market	1943.3
Slum	2176.8
Hotel	2286.3
High Class Society	2163.7
Middle class society	2102.2
Low class society	1877.5
Institute and College	2260.0
Community /marriage hall	2205.0
Dumping Site	2500.0
Average Value	Greater than 1650

Details of installed units The details of units is as follows-

Table 9. Details of WTE Projects

Sr.	Name of unit	Capacity	Purpose	Water pollution control	Air pollution control	
no.				arrangement	arrangement	
1	Waste	600 TPD	To reduce the waste	STP of 40 KLD capacity	Flue gas treatment system	
	Incineration plant		volume and generate	based on UASB reactor	(FGT) and Fabric filters are	
	(11.5 MW)		electricity out of	technology has been	provided along with providing	
			MSW.	provided.	stack height of 50 meter.	





Fig. 8 Indicative Longitudinal Section of Waste to Energy Plant, Jabalpur

Jabalpur Waste to Energy Plant:



















Photo 9





Photo 10

E. Integrated solid waste management project Bhopal

Name of Project: Development of an Integrated MSW Processing and Disposal Facility at Adampur Chhavni, Bhopal by M/s. Green Resources Solid Waste Management Pvt. Ltd.

Location of Project: Adampur Chhavni, Raisen road - Bhopal (M.P.)

Latitude and Longitude: (23°15'55.6"N 77°33'33.3"E) or(23.265452 N, 77.559256 E)

Site Layout:



Fig. 11 Site layout plan of Integrated Solid Waste Management Facility, Bhopal



F. Feasibility of Project (why this technology is adopted)

Safe disposal of municipal solid waste being generated in the ULBs is necessary as per SWM rules 2016. The project aims to manage the solid waste of Bhopal Municipal Corporation in integrated manner so as to minimize the likely environmental impact and efficiently utilize the waste as a resource wherever it may be possible. The project helps in generating RDF (Refuse Derived Fuel) which is to be used for energy recovery and organic fraction is being converted into compost by windrow composting which is further utilized /sold to farmers for horticulture / agriculture purposes. Thus such a facility is beneficial for handling MSW in efficient manner following 4R principal (Reduce, Reuse, Recycle & Recover) and hence it is cost effective/economical as well.

G. Area covered by ISWM Facility

The ISWM facility is handling MSW of Bhopal Municipal Corporation only. An indicative Google map of Bhopal city is given below:



Fig. 12 Indicative Google map of Bhopal City of Madhya Pradesh

H. Quantity of solid waste

At present the daily amount of MSW being collected is approximately 800 TPD however the plant capacity for projected population is about 1000 TPD. Out of this collected MSW the daily amount of RDF being generated is about 200 TPD and finished compost of good/desirable quality is about 100 TPD. Apart from this recyclables obtained in the range of 7 TPD whereas inert material quantity going to landfill is approximately 50 TPD.

I. Characteristics of solid waste

Mixed type of waste is being sent to the facility which contains food waste, vegetable waste, fruit peels, plastic waste, metals and inert waste etc. Approximate physical composition of waste is given below: Table 10

Table 10				
Waste Component	% share			
Food, vegetable& other organic waste	54			
Textile	6			
Paper, cardboard	7			
Plastic and Polythene	13			
Glass & Ceramic	2.5			
Rubber & Leather	3.5			
Wood	2			
Stones & Bricks	11			
Metal	1			
Total	100%			

Details	of	installed	units.	Table	No	11
Detans	UI	mstancu	unus.	Lanc	110	**

Sr. no.	Name of unit	Capacity	Purpose	Water pollution control arrangement	Air pollution control arrangement
1	Compost plant (windrow composting)	500 TPD	To produce compost of good quality from organic fraction of municipal solid waste	The processing of waste is done under shade and leachate collection system is provided. Leachate treatment plant (LTP) will be installed soon to treat excess amount of leachate.	The processing of waste is being done under covered shade and to mitigate the odour problem organic chemicals are sprayed over the waste daily.
2	RDF Processing unit	500 TPD	To produce RDF which may utilized further for energy recovery	Leachate collection system is provided.	The processing /sorting is done under covered shade.
3	Recyclables	20 TPD	To recycle the plastic, metal, wood, glass and other recyclable fraction of the waste.	Recyclable fraction will be given to recyclers for processing.	Recyclable fraction will be given /sold to recyclers for processing and reuse.
4	Sanitary landfill	50 TPD (Area of landfill is 5 acres)	To dispose off leftover waste in secured manner, which cannot be reused or further processed.	HDPE liners are provided on the base and daily cover is applied in secured manner. Leachate collection system is also there.	Daily cover is applied.
5	Bio-mining	2000 TPD	To handle the legacy waste already dumped at the site	Leachate collection system is provided.	Covered boundary is there along with green belt.

Photographs of installed units are given below:

Compost Plant:

Retrieval Number: 100.1/ijmh.K15010781122 DOI: <u>10.35940/ijmh.K1501.0781122</u> Journal Website: <u>www.ijmh.org</u>











RDF Processing unit:





Recyclables/ Material Recovery Facility:





Sanitary Landfill:

Published By: Blue Eyes Intelligence Engineering & Sciences Publication (BEIESP) © Copyright: All rights reserved.





Bio-mining Facility for legacy waste treatment:







V. CONCLUSION

The study on integrated municipal solid waste management sites has given certain key outcomes related to feasibility, municipal waste management techniques, relative environmental impacts, economic considerations etc., on the basis of which it may be concluded that in order to manage the municipal solid waste in an integrated manner it is better to have integrated setup including compost plant for handling organic fraction of the waste and waste to energy plant for handling dry fraction of the waste. Wherever cement plants are situated in nearby locations (preferably within 100 km radius) at those locations RDF may be disposed off though energy recovery at cement kilns or may be transported to nearby waste to energy plant instead of setting up own WTE plant in order to maintain economic feasibility and to avoid any burden of capital investment. Further it is noteworthy to say that there are other waste to energy technologies including Plasma Arc Gasification technique which is used in many countries for handling MSW but in Indian scenario it is not that much beneficial taking into account cost considerations.

A comparative analysis of four ISWM facilities of Madhya Pradesh at different locations under study is concluded below: Table no. 12

Sr. No.	Comparison parameter	Integrated Solid Waste Management Facility Village- Pahadiya Distt. Rewa (MP)	Integrated MSW Processing and Disposal Facility, at Padarwara, Katni (MP).	Integrated MSW Processing and Disposal Facility, at Adampur Chhavni, Bhoapl (MP)	Waste to Energy Plant (11.5 MW) at Village Kathonda, Jabalpur (MP)
1	Technology for handling MSW	Windrow composting for managing organic fraction and waste to energy plant for handling combustible fraction (RDF) of MSW. Inert ultimately going to landfill.	Windrow composting for managing organic fraction of MSW and combustible fraction (RDF) is sent to other WTE Plant for Energy Recovery.	Windrow composting for managing organic fraction of MSW and combustible fraction (RDF) is sent to other WTE Plant and cement plants for Energy Recovery.	Mixed waste/un- segregated waste is handled by incineration of waste in controlled conditions and thereby energy recovery.
2	Economic Consideration	Initial capital expenditure is high due to higher cost of waste to energy plant. However cost may be recovered by selling electricity generated.	Capital expenditure is at moderate level and some recovery is done through selling compost.	Capital expenditure is at moderate level and some recovery is done through selling compost.	Capital expenditure is at high level however recovery is possible through selling generated electricity.

3	Time requirement for handling daily waste	For composting nearly one month is required. For RDF handling on an average one day will be required.	For composting nearly one month is required. For RDF handling on an average one day is required.	For composting nearly one month is required. For RDF handling on an average two days are required.	MSW is processed within a day.
4	Capacity to Handle MSW	350TPDwetwaste/organicwasteand500TPDdrywaste(RDF)	150 TPD Wet Waste and dry waste /RDF content as may be present in MSW	1000 TPD Wet Waste and dry waste /RDF content as may be present in MSW	600 TPD Mixed waste.
4	Land/ Space Requirement	Larger area is required because of landfills.	Larger area is required per unit MSW processed because of landfills.	Larger area is required per unit MSW processed because of landfills.	Less area of land is required.
5	Transportation requirement	Collection and transportation of MSW form door to door to ISWM site Pahadiya, Rewa. After processing waste is disposed in the premises. However at present WTE plant is under construction hence RDF is sent to nearby cement plants.	Collection and transportation of MSW form door to door to MSW processing site. After processing waste is disposed in the premises and the RDF content is sent to nearby waste to energy plant in Jabalpur (MP).	Collection and transportation of MSW form door to door to MSW processing site at Adampur Chhavni After processing inert waste is disposed in the landfill and RDF content is sent to nearby cement plants.	Collection and transportation of MSW form door to door to WTE plant at Kathonda Jabalpur. After incineration no significant waste is there for transportation.
6	Leachate problem	Leachate is to be handled in Leachate treatment plant	No Leachate is observed. Moreover, Leachate collection system is provided.	Leachate is collected in separate tank and re- circulated back to windrow to increase composting activity. Leachate treatment plant is proposed.	No Significant leachate problem.
7	Odour Problem	Odour problem is not significant however ecosorb/organic chemicals are sprayed to mitigate odour problem.	Odour problem is not significant	Mild odour problem is observed however dense plantation is being done in periphery.	Odour problem is not significant
8	Inert and Ash Handling	Inert and ash is to be disposed off in landfill.	Inert is to be disposed off in landfill, no ash generation is there.	Inert is to be disposed off in landfill, no ash generation is there.	Ash is to be disposed off in secured landfill.

Thus apart from above, it may also be concluded that in case of cluster based projects as well as for large cities further studies on route optimization to reduce the travel distance may be helpful in reducing the overall cost of waste collection and transportation.

ACKNOWLEDGEMENT

We are very much thankful to all faculty members of vedica institute of technology RKDF Univercity Bhopal for valuable guidance and support for this paper.

REFERENCES

- Alan BL, VP Cruz, M papay and GJ Trezek, scavenging in metro manila March – 1982 the metro manila solid waste management study task 11
- 2. Associated press " refuse Kil 13" the times, London 1993, Thursday april 29th : 15
- Advanced plasma power 2007'' Gas plasma out puts clean syngas the effects of plasma treatment on the reduction of organics species in the syn -gas
- Anh N p, change kook R, vida NS, Jim S 2008, characterisation of slow pyrolysis products from segregated waste for energy production J Anal Appl Pyrol 81 (1) 65-71.
- 5. Begchi (1994) " Design construction and mentoring of landfills"" John wiley and sons new York.
- 6. Bhide A.D., and surendersan, BB (1987) solid waste management in developing countries" INSDOC, New Delhi.
- Bhide AD (1993) "Biogass from Land fills" civil engineering and construction review., February 1993 PP 47-49 [CrossRef]
- Bhide A.D. and sumdarsan 1987 " solid waste management n developing countries "" INSDOC New Delhi
- Birley M.H. "The Health impact assessment of development projects" The Health Impact programme, Liverpool school of tropical medicine pemprookke place Liverpool L35QA London December 1994.
- Birgg D, Corvalan C, Munminem M " linkage Methods for environment and health analysis general guidelines" office of global

Retrieval Number: 100.1/ijmh.K15010781122 DOI: <u>10.35940/ijmh.K1501.0781122</u> Journal Website: <u>www.ijmh.org</u> and integrated environmental health, WHO Geneva 19996- a joint publication of UNEP, USEPA and HWO

- 11. Bubel AZ "waste picking and solid waste management "envir san rev. 1990, 30 : 53-66
- Beaven RP and W powrie "Hydro geological and geotechnical properties of refuse using a large scale compression cell" proceeding s of the fifty international land fill symposium volume II Cagliari Italy 1995.
- Beukering (1999) Waste recovery in Bombey : a socio economic and environmental assessment of different waste management option, third world planning review 19 (2) PP 163-187 [CrossRef]
- Burton JM sustainable waste management a case study from the UK water industry water sci technol 1998 38 51-8 [CrossRef]
- Boyli CA solid waste management in New Zealand waste management 2000. 20. 517 – 26. [CrossRef]
- Cal recovery, Inc, Handbook of solid waste Properties government advisory associates inc, New York, New York USA 1993,
- 17. Cal recovery, INC, solid waste management options in Americans samoa, prepared for national renewable energy laboratory march 1994
- Cal recovery, metro manila, solid waste management study waste stream characterization prepared for Adhoc committee, republic of the philipines May 1982
- 19. CPCB, "study on plastic waste disposal through plasma pyrolysis technology" October 2016.
- CPCB, "selection criteria for waste processing Technologies" (Aug 2016) [in compliance with national green tribunal order dated 25th may & 1st Aug. 2016 in the matter of O.A. No. 199 & 2014 Almitra H. patel & Anr. Vs union of india & ors.]
- 21. Circeo et. al of (1997) evaluation of Plasma arc Technology for the treatment of municipal solid waste in Georgia" The construction research centre, collage of architecture, Georgia institute of technology, Altgnta, Georgia tech research institute Atlanta georgia Jan 1997 PP 72.
- 22. Capacity To ACT IN INDIA'S solid waste management and waste to energy industries bhada Perinzsl columbia univ. December 15, 2005
- Composting waste management living green UF/IFAS extension . http://liveinggreen.ifasufp.edu[online] June 5, 2007 [sited Nov. 2011]





- 24. Caroline Ducharme, Technical and economic analysis of Plasmaassisted waste to Energy processes department of Earn and Environmental Engineering Fu foundation of engineering and applied science Columbia univ. Sep. 2010. [CrossRef]
- 25. Consonnis Giugliano M, Grosso, M 2005 alternative strategies for energy recovery from municipal solid waste part A mas and energy balances, waste management 25 123-135 [CrossRef]
- 26. Diaz L.F., G.M. Savage and C.G. Golueke, resource recovery from municipal solid waste vol I primary processing, CRC republishes Inc. Boca Ratn Florida USA 1992.
- 27. Diaz L.F. G.M. savage, L.L. Eggerth and C.G. Golueke composting and recycling municipal solid waste lewis. republisher annanbor, Michigan, USA 1993
- 28. Diaz L.F. C.G. golueke "solid waste management in developing countries Bio cycle 26: 46-52 September 1985.
- 29. Danial, D.E. (1993) : Geotechnical practice for waste disposed" chapman and hall, London
- Datta, M (1997) waste disposed in engineered landfills" Narosa 30. Publishers Delhi.
- 31. Dodge, Ed Plasma gasification of waste newyork cornall university -Johnson Graduate school of management 2008.
- 32. Dighe Shyam V. 2008 Westinghouse plasma carporation medison. pennsylvania USA, plasma gasification: a proven technology, proceedings of NAWTEC 16th Annual North American waste to Energy conference may 19-21 2008 Philadelphia Pennsylvania USA. [CrossRef]
- 33. Environmental Pollution Control in relation to development (1985) world health organization technical report series no. 178
- 34. cole" chemical and biological exposure and safety hazards in medical waste treatment facilities: An assessment of alternative Technology" Vol 98/2 No. 9 (Cedex, France: international healthcare waste network Aug 31, 1998.
- 35. Ecke H, sakanaluera H. Matsuto T, Tanaka N, Lagerk V. ist. A 2000 State of the arc treatment processes for municipal solid waste incineration. [CrossRef]
- 36. Ed. Digemcarnell university johnson graduate school of management queens university school of business. Plasma gasification, clean renewable fuel through vaporization waste July 2008
- Edbertho leal quiros 2004, plasma processing of municipal solid watste 37. Brazilian journal of physics, 34 (4B) PP 1587. [CrossRef]
- 38. Evans steave D, (2009) Plasma gasification plants benefits for municipal waste management, ezine Articles. Com available at http://www. Articalesbas.com/istructurearticals/plasma-gasification plants befits - for municipal - waste management.
- 39. G gunatileke Ed. " health dimensions of economic reform" (World Helth organization Geneva (1992)
- 40. Guideline for management and handling of hazardous waste' MOEF 1991 Delhi.
- 41. Grisolia M.Q. Napoleoni and G Tangradi "Contribution to a technical classification of MSW" Proceedings of the fifth international land fill symposium vol. 2 cagliari itali 1995.
- 42. Gomez, E, Amutha RD, Cheeseman CR, Deegan D, wise Boccaccini, AR 2009, Thermal plasma technology for the treatment of waste a critical review J Hazard mater 161 (2-3) 614 - 26 [CrossRef]
- 43. Grimshaw A.J., and Lago A 2010 small scale energy.Gasification Technology 3rd International symposium on energy from Biomass and Waste venice Italy 8-11 No. 2010 Cisa publisher Italy - ISBN 978 -88-6265-008-3

AUTHOR PROFILE



Bundela S. Varun, B.E. (Civil Engg.) From Ghyan Ganga institute of technology Jabalpur M.E. (Environmental Engg.) From S.A.T.I. Vidisha. Presently working as a assistant professor in Bansal institute of technology anand nagar Bhopal.



Dr. Arun Patel, Ph.D, M.Tech (Hons), BE, Civil Engineering Ph.D. in Geoinformatic under Civil Engineering Department from Maulana Azad National Institute of Technology (MANIT), Bhopal. Mater of Construction Technology and management (Civil Engineering) with 79.4% from S.A.T.I Vidisha. Bachelor

of Engineering (CIVL Engineering) from College of Engineering and Technology Akola



Retrieval Number: 100.1/ijmh.K15010781122 DOI: 10.35940/ijmh.K1501.0781122 Journal Website: <u>www.ijmh.org</u>

Published By: